

	H55	P92
MODEL NUMBER	L	XL
SIZE	55" (140cm)	92" (234cm)
IMAGE DIAGONAL SIZE	35" (89cm)	43" (110cm)
IMAGE HEIGHT	41" (104cm)	81" (206cm)
IMAGE WIDTH	46.2"x11.1"x7.9" (117x28x20cm)	16"x10"x96" (41x25x243 cm)
HELIO BASE DIMENSIONS	~25.5 lbs (11.5 kgs)	~60 lbs (27 kgs)
HELIO BASE WEIGHT	11.2"x8.7"x1.8" (28x22x4.7cm)	11.2"x8.7"x1.8" (28x22x4.7cm)
PROJECTION MODULE DIMS	4.6lbs (2.1 kgs)	4.6lbs (2.1 kgs)
HELIO PROJECTION WEIGHT	●	●
TRANSLUCENCY CONTROLS	+/- 30 deg	+/- 30 deg
PROJECTION ANGLE	~180 deg front	~180 deg front
VIEWING ANGLE	210W (proj) 80W (base)	210W (proj) 250W (base)
POWER CONSUMPTION	3000 (lumens at source)	4000 (lumens at source)
BRIGHTNESS	base unit & projection unit	base unit & projection unit
COMPONENTS	16.7 million	16.7 million
COLORS	1024x768 (supports 1600x1200)	1024x768 (supports 1600x1200)
RESOLUTION	480i/480P/720P/1080i/1080p	480i/480P/720P/1080i/1080p
FORMATS	NTSC/PAL/SECAM	NTSC/PAL/SECAM
MATERIAL	aircraft aluminum & plastic	aircraft aluminum & plastic
PROJECTION THROW DISTANCE	36"-100" ( 91cm-254cm )	60-200" (152cm-508cm)
REFRESH RATE	85Hz V, 91KHz H	85Hz V, 91KHz H
VOLTAGE	international 90-240v 50/60 Hz	international 110/240v 50/60 Hz
LCD CONTROL PANEL	2 line display	4 line display
CONTROLS	one button	one button
LEVEL SENSOR	analog & digital	digital
CONSUMPTION	0.1-0.15L hr	0.2-0.25L hr
TANK SIZE	3L (external request)	25L /external
REMOTE TRIGGER RELAY	(request option)	(request option)
AFFECT ENVIRONMENT	no	no
OPERATING TIME	12 hrs ok	12 hrs, 24 hrs ok
TOUCHSCREEN	display only	display only
THUMB-DRIVE FILE UPLOAD	optional \$500	●
SOUND LEVEL	~44dB (@2m)	~49dB (@2m)
ADDITIONAL INPUTS	VGA/Svideo/USB drive	VGA/Svideo/USB drive
ORIENTATION	up	up or side
OPERATING ENVIRONMENT	0%-99% non condensing RH	0%-99% non condensing RH
OPERATING TEMPERATURE	40F-95F (4C-35C)	40F-95F (4C-35C)
REMOTE CONTROL	●	●
RS-232 PROJECTOR	●	●
TEMPORARY OR INTEGRATION USE	temporary use	temporary & integration use
LEAD-TIME	1 week (typ.)	2-3 weeks (typ.)
INTERNATIONAL SHIPPING	●	●
ACCESSORIES	cables, CD, manuals included.	cables, CD, manuals included.
PROJECTOR/ POWER CERTIFICATIONS	CE,FCC,N78,MET /BASE CE	CE,FCC,N78,MET /BASE CE
WARRANTY	5 yrs limited	5 yrs limited

ACCESSORIES	
RS-232 CABLE BASE UNIT	\$40
RS-232 CABLE PROJECTION	\$40
REPLACEMENT DISK	\$5
EXTRA FILTER	\$10
REPLACEMENT BULB	\$450
EXTERNAL TANK W/ DIGITAL LEVEL	\$150



PRICE

\$18,500

\$65,000



\*all information to be accurate at time of printing and subject to change

sales@io2technology.com

WWW.IO2TECHNOLOGY.COM

